

## **Hydraulic Machine Control System**

Hydraulic Machine Control System PHS-360W


## **Hydraulic Machine Control System**

## **Double Elevation Machine Controller**

## **PHS-360W**


Only to set the receiver on the mast and to connect by the cables, it enables to control the blade automatically. Two laser receivers can be used as an option.


- Double elevation control.
- Two-way controls in manual or automatic.
- Double elevation display with hyper-brightness LED.
- Proportion time value control.
- Vibration-proof, shock-proof and rainwater-proof.











A unit includes one receiver. As its option, two receivers are available as above figure

Horizontal LED	Green	
High/low LED	Red	
Input voltage	DC12V	
Maximum current	5A per driver	
Valve compatibility	Proportion time(PT)valve control	
Power	External DC12V	
Size	270×168×118mm(with a fitting handle)	
Weight	About 1.8kg	
■ Specification		
Detecting range	300m*	
Receiving angel	360° receive at all directions	
Detecting window	200mm	
Detecting accuracy	Fine measuring ±2.5mm	
	Coarse measuring ±5mm	
Water proof	Yes. IP65	
Temperature range	-10°C∼50°C	
Power	External +12V	
Size	206×96×300mm	
Weight	About 2.7kg	



**5** Corporation 1-1603 Kounosu,Tenpaku-Ku, Nagoya 468-0003 JAPAN Tel:81-52-847-8880 Fax:81-52-847-8883

www.argenlaser.com

DUE TO PRODUCT IMPROVEMENT. THE SPECIFICATION & THE APPEARANCE MAY CHANGE WITHOUT ANY NOTICE

Representante en Sudamérica: ARGENLASER S.A.